

The economical CX3 alternative
for all applications



Cabelcon is now offering CX3 HP, a more competitive solution with superb electrical and mechanical characteristics as the original CX3.

CX3 HP is a true Cabelcon quality product, featuring all the well-known Cabelcon CX3 performance capabilities. The only difference is that the brass shell is replaced by a UV stabilised High Tech Polymer solution supported by a brass ring at the end - still keeping it very strong and resistant to corrosion and UV radiation. The brass sleeve and the nut is of course Nitin-6™ plated.

Use the CX3 HP for CATV, satellite LNB's, receivers, cable modems, set top boxes and all other applications where you are using the original CX3.



- Strong UV resistance
- Operational to above 3 GHz
- Standard Cabelcon colour coding
- Built-in foil prep tool in the front
- Shell material is a High Tech Polymer
- One-piece connector – no loose parts
- Waterproof tested to 30 meter / 8 hours
- Professional quality and excellent performance
- Fits standard RG6 & 59 cables (size 3.7 - 3.9 - 4.9 - 5.1)

Technical Data (Typical)

Operational to 3 GHz	
Impedance	75 Ω
Shielding Eff. 30 - 3000 MHz	130 dB
Transfer Imp. 5-30 MHz	2.5 mΩ/m
Return loss 0.3 - 500 MHz (typ)	46 dB
Return loss 500 – 1000 MHz (typ)	46 dB
Return loss 1000 – 3000 MHz (typ)	40 dB
IMD (3 rd order@2x100mW)	-147dBc
IMD (IP3 value)	+100 dBm
AMP rating	cable data
Max. Tensile strength (overall)	235 N

Ordering information

F-59-CX3 HP 3.7	99909016
F-59-CX3 HP 3.9	99909021
F-56-CX3 HP 4.9	99909041
F-56-CX3 HP 5.1	99909046